



Size	mm	80x5
Inch		3"x2

All Dimensions Are In mm

* Deep Stuffing Box

- * Gland Seal Design
- * Graphite Ring End



Do Not Copy Drawing
©COPYRIGHT

JKE

DESIGN STANDARD		API 600/API 603		PRESSURE TESTING - 300# RATING	
BODY SHELL DESIGN		API 600/ASME B 16.34		YES @ 79.0 KG/CM ²	
FLANGED END		ASME B 16.5, 150# RF		YES @ 58.0 KG/CM ²	
FACE TO FACE		ASME B 16.10		YES @ 5.0 KG/CM ²	
LEAKAGE CLASS		CLASS IV (4)		YES @ 21.0 KG/CM ²	
PROCESS FLOW MEDIA				JACKET PASSING MEDIA	
DESIGN		***		DESIGN	
PRESSURE		KG/CM ²		KG/CM ²	
OPERATING		**		OPERATING	
DESIGN		KG/CM ²		KG/CM ²	
TEMP.		*** °C		TEMP.	
OPERATING		*** °C		OPERATING	
PAINTING		MANUFACTURER STD		PMI	
COLOR		MAIN/ACTUATOR STD		NDE/PT/RT	
TAG NUMBER		***		NACE	
				Nde Required	
				Nde Required	
				Nde Required	

[illegible]

	JACKET IN/OUT SIZE	JACKET DRAIN SIZE	
THREADED END NPT	☒ 1/2" ☐ 3/4" ☐ 1"	☒ 1/2" ☐ 3/4" ☐ 1"	3000 PSIG RATING
THREADED END BSP	☐ 1/2" ☐ 3/4" ☐ 1"	☐ 1/2" ☐ 3/4" ☐ 1"	3000 PSIG RATING
FLANGED END RF 150#	☐ 1/2" ☐ 3/4" ☐ 1"	☐ 1/2" ☐ 3/4" ☐ 1"	
FLANGED END RF 300#	☐ 1/2" ☐ 3/4" ☐ 1"	☐ 1/2" ☐ 3/4" ☐ 1"	
FLANGED END RF 600#	☐ 1/2" ☐ 3/4" ☐ 1"	☐ 1/2" ☐ 3/4" ☐ 1"	
ANY SPECIAL	☐		



MADE IN AUSTRIA

NO.	ITEM	MATERIAL
17	JACKET COUPLING/FLANGE	A 105
16	JACKET	A 216 GR WCB
15	HAND WHEEL NUT	CARBON STEEL
14	HAND WHEEL	5 G IRON
13	BOHNETT STUD AND NUT	A 193 GR B7/A 194 GR 2H
12	BOHNETT NUT	CARBON STEEL
11	STEM NUT	CARBON STEEL
10	GASSET	SPW GRAPHITE FILLED GRAPHITE (IGRATOL)
9	GLAND PACKING RING	CARBON STEEL
8	GLAND FLANGE	CARBON STEEL
7	GLAND BUSH	A 276 T-410 (SS 410)
6	BACK SEAT BUSH	A 276 T-410 (SS 410)
5	STEM (SPINDLE)	A 276 T-410 (SS 410)
4	WEDGE (GATE)	CAL51WC+B 13K GR. FACE
3	SEAT	CS-STELLITE HARD FACE
2	BOHNETT	A 216 GR WCB
1	BODY	CARBON STEEL

Client:  FULL JACKETED GATE VALVE, FLANGED END, 300#, WHEEL OPERATED

Exclusive Jacketed Valve Manufacturer
(For all types of Jacketed Valves/All sizes/All grades/All materials)
Ahmedabad, Gujarat, INDIA.

www.JacketedValvesManufacturer.com

QUOTATION/ENQ. NO. :

DRG. NO. : JKET/FOS/CGT300

	m	
--	---	--

[illegible]