

7

Dimensions [150 Class]

		PRESSURE TESTING - 150# RATING			
DESIGN STANDARD	API 599/BS 5353/API 6D	HYDRO BODY		YES @ 30.0 KG/CM2	
BODY SHELL DESIGN	ASME B 16.34/API 599	HYDRO SEAT		YES @ 21.0 KG/CM2	
FLANGED END	ASME B 16.5, 150# RF	PENIMATIC SEAT		N.A.	
FACE TO FACE	ASME B 16.10	HYDRO JACKET TEST		YES @ 10.0 KG/CM2	
LEAKAGE CLASS	CLASS IV				
PROCESS FLOW MEDIA		JACKET PASSING MEDIA			
PRESSURE	DESIGN *** KG/CM2	PRESSURE		DESIGN *** KG/CM2	
	OPERATING *** KG/CM2			OPERATING *** KG/CM2	
TEMP.	DESIGN *** °C	TEMP.		DESIGN *** °C	
	OPERATING *** °C			OPERATING *** °C	
PAINTING	PROCEDURE MANUFACTURER STD.	PIM		Not Required	
COLOR	MANUFACTURER STD.	NDE/DPT/RT		Not Required	
TAG NUMBER	***	NACE		Not Required	
TYPE AND SIZE OF JACKET CONNECTION		REMARK			



Title: FULL JACKETED (PTFE Sleeved) PLUG VALVE FLANGED END, 150# (With OVERSIDE Flange)	Client: (With OVERSIDE Flange) 
---	---

Do Not Copy Drawing
©COPYRIGHT

☒ For Reference
☐ For Approval
☐ For Record

DATE : 01/04/2023